

GUNNEBO ROV OPERABLE SHACKLES | TECHNICAL SPECIFICATION



WLL (tonnes)	9,5 - 12 - 17 - 25 - 35 - 55
Weight in Kgs	From 6,5 to 40 kgs
Standard	Dim. According to EN 13889
Safety Factor	6:1
Material	High tensile steel, quenched and tempered
Finish	All load bearing parts hot dip galvanized
Marking	All Shackles have unique marking

- The ROV Operable Shackle is designed for smooth and easy use in subsea lifting and rigging operations.
- It has no loose parts, in closed and opened position, and there is therefore no need for wires or monkey fists that will risk snagging or getting in the way.
- The high visibility handles are Close-die forged and has double safety functions - Shark tooth locking with indicator that will show if the shackle is in open or locked position as well as the spring loaded handle.
- The handle is the same size, regardless of size of shackle.
- The ROV Operable Shackle no 861 is an easy to operate shackle, saving valuable time and money.

CONTACT

E-mail: post@sagasubsea.no | Tel: +47 52-SUBSEA (52 78 23 32) | +47 906 94 490



Saga Subsea AS | Skillebekkgaten 1 | Killingøy Offshorebase | NO-5523 HAUGESUND | Norway

Tel: +47 52-SUBSEA (52 78 27 32) | +47 906 94 490 E-mail: post@sagasubsea.no
