

## SAGA PARROT SCISSORS ICU 40 a 30 | TECHNICAL SPECIFICATION



<b>Max Hydraulic Inlet Pressure / RPM</b>	<b>Mpa 500 / 50</b>
<b>Max Cutting Opening</b>	<b>181 mm</b>
<b>Max Cutting Force</b>	<b>Kn/t 644 / 65,7</b>
<b>Required Oil Content (effective)</b>	<b>Cc 163</b>
<b>Weight in Air</b>	<b>19,5 KGS</b>
<b>Dimensions (LxWxH)</b>	<b>775 x 270 x 218 mm</b>
<b>Outer dimensions Jaw</b>	<b>Fully open: 275mm Fully Closed: 150mm</b>

### **SAFETY NOTE!**

- \*Never perform deck checks or pre-dive without correct PPE, included eye protection, where all personnel to keep good distance and never to be positioned parallel to the cutter while tool is running.
- \*During operation, the tool shall be started with as low hydraulic pressure and flow as possible
- \*At NO circumstance shall the tool be handled by personnel while being operated
- \*Remember to always check for loose bolts or nuts before commencing deck checks or operation
- \*Only authorized personnel are to operate this tool

### **CONTACT**

E-mail: [post@sagasubsea.no](mailto:post@sagasubsea.no) | +47 52-SUBSEA (52 78 27 32) | +47 906 94 490